




# GREEN ENERGY NETWORK



Regd. Office:-H.No.1534/C-101 Parmar Nagar Co.Op.Hsg.Soc. At Bhuvaneshwar,  
Post Varse, Tal.Roha-Raigad Maharashtra 402109 India. 8308378882/9422094430

**TDS**

## 3R LIGHT - SMD LED LUMINI LIGHT ECO 4 FEET - 30 W



### Product Specification

Name	30 W Lumini Fitting
Model No	GELUMINI-30-4FT-E1
Doc.No	GELUMINI-30-4FT-E1/ 2
Date	15/02/2019.

### Application

Inspection Table	Engineering Shop
Office Light	Food Plant


### Technical Specification of Energy Efficient 30 W SMD LED Lumini Light ( 04 Ft ) - 3R LIGHT.

Characteristics	Standred Value
Luminaries Wattage	30 Watt ( ± 5% )
Luminaries Input Voltage	230 Voltage
Luminaries Input Frequency	50 Hz
Luminaries Input Current	0.145 Amp.
Luminaries Power Factor & THD	>0.95 <10%
Luminaries Efficiency	>86.5%
Luminaries Light Spreing Angle	120°
Luminaries Temperture Class	T 6
Luminaries IP Standred	Indoor IP 20
Luminaries Total Weight	1.5 kg. ( Approx )
Luminaries Starting Time	Rapid (.4 Sec.)
Luminaries Warrantly	3 Years
LED Make	Everlite / Seoul
LED Certification	LM 80
LED Lamp Type	SMD ( 2835 )
LED Lamp Lumen @25 Degree C	2700
LED Lamp Lumen Efficacy (Lm/Watt)	100 Lu/Watt
LED Lamp CCT/ Color Rendering Index	6500 K / RA 80 Min
LED Lamp Wattage/ Current / Voltage	27 W / 750 mA / 36.4 V @ Tc 25 Degree C.
LED Lamp Life	50,000 Hours Min.
LED Lamp Identification Feature	TDS
Actual test report of LED Lamp	Actual Operating test Report for 50,000 Hrs.
Driver Type	Constant Current ( CC ) Mode
Driver Input Voltage Range	90 ~ 305 V AC
Driver Frequency Range	47 Hz - 63 Hz
Driver Output Protection	Short Circuit, Over Voltage, Surge
Driver Surge Protection	Inbuilt 4 KV
Luminaries Junction Temperature - Tj	< 80 Degree C.
Luminaries Case Temperature - Tc	< 74 Degree C.
MOC- Heat sink	Aluminium Extrusion - LM -06



Regd.Office:-H.No.1534/C-101 Parmar Nagar Co.Op.Hsg.Soc. At Bhuvaneshwar,  
Post Varse,Tal.Roha-Raigad Maharashtra 402109 India. 8308378882/9422094430

## Schematic Drawing



- All Technical Parameterrs & Drawing consider + - 05%

### 3R Light SPECIALITY :

This Fixure is providing required spreaded illumination level without Glare through diffused light.  
3R Light products are having Precise Thermal management for longer life and Precise light spreading angle for required illumination.

- Information & Product Change With Out Any Notice

Prepared By

Reviewed By

Approved By

### SALES & MARKETING OFFICE

SHOP NO.03 & 04, SUNCITY GARDEN PHASE NO.01, BEHIND NAVRATNA HOTEL, AT BHUVANESHWAR, POST- VARSE TAL. ROHA,  
DIST-RAIGAD, MAHARASHTRA 402109 INDIA. PH.NO.02194-233900, 8308378882, 8308378252

Email: [sales@genlights.in](mailto:sales@genlights.in), Web: [www.genlights.in](http://www.genlights.in)

### FACTORY I

686, AT POST MEDHA, HANUMANT ALI, NEAR BHAIRI TEMPLE, TAL- ROHA, DIST-RAIGAD, MAHARASHTRA 402109 INDIA.

### FACTORY II

SHED NO.9/10/11, SURVEY NO.298/1, NEAR L-230, NAGAPUR MIDC, AHMEDNAGAR 414111