



GREEN ENERGY NETWORK



Regd.Office:-H.No.1534/C-101 Parmar Nagar Co.Op.Hsg.Soc. At Bhuvaneshwar,
Post Varse,Tal.Roha-Raigad Maharashtra 402109 India. 8308378882/9422094430

TDS 3R LIGHT - COB FLAMEPROOF RETROFIT KIT - 30 W (ECO)



Product Specification

Name	Retrofit Kit - Flame Proof Well Glass
Model No	GENRETRO-30
Doc.No	GENRETRO-30
Date	30/04/2021.

Warranty

Chemical Industries	Oil Refinery
Mining Industries	Hazardous Industries
Petro Chemical Industries	Pharma Industries

Technical Specification Of 30 W Flameproof Wellglass Retrofit Kit - COB Eco - 3R LIGHT

Characteristics	Standred Value
SYSTEMS Wattage	30 Watt (± 5%)
SYSTEMS Input Voltage	240 Voltage
SYSTEMS Input Frequency	50 Hz
SYSTEMS Input Current	0.4 A.
SYSTEMS Power Factor	>0.95 THD - < 10%
SYSTEMS Efficiency	86%
SYSTEMS Light Spreding Angle	60° / 90° / 120° / Diffuse Degree (Default Diffuser Lens)
SYSTEMS Temperture Class	T 6
SYSTEMS IP Standred	Outdoor IP 66
SYSTEMS Total Weight	1.2 Kg (Approx)
SYSTEMS Starting Time	Rapid .4 Sec.
SYSTEMS Warranty	02 - 03 Years
LED Make	Citizen / Bridgelux
LED Certification	LM 80
LED Lamp Type	COB
LED Lamp Lumen @25 Degree C	3974
LED Lamp Lumen Efficacy (Lm/Watt)	160 - 165 lm / W
LED Lamp CCT/ Color Rendering Index	6500 K / RA 80 Min
LED Lamp Wattage/ Current / Voltage	27.6 W / 750 mA / 30 - 42 V @ Tc 25 Degree C.
LED Lamp Life	50,000 Hours
LED Lamp Identification Feature	Unique Sr.No on each LED.
Actual test report of CITIZEN LED Lamp	Actual Operating test Report for 50,000 Hrs.
Driver Type	Constant Current (CC) mode
Driver Input Voltage Range	90 ~ 305 V AC
Driver Frequency Range	47 Hz - 63 Hz
Driver Protections	Input Over Current : NON - Resettable Input Over Voltage : Cutoff @ Vin 3 0±10Vac, Auto Recovery Immunity - 440Vac for 48 Hours Input Under Voltage : Shutdown < 100Vac, Auto recovery Output Short Circuit : Auto Recovery (HICCUP MODE) Output Open Circuit : Auto Recovery (HICCUP MODE) Output Overload : Yes Over Temperatur : Yes
Driver Surge Protection	Inbuilt 04 KV (As per EN 61000-4-5)
Driver Service Life	50,000 Hours @ Tc Max
Luminaries Juction Temperature - Tj	< 84 Degree C.
Luminaries Case Temperature - Tc	< 60 Degree C.
MOC- Heat sink	Aluminium Casting - LM -06

Prepared By

Reviewed By

Approved By